



ATEX 95 Rated  
150 m<sup>2</sup> insect  
control unit



## I-TRAP 150EX LED

WALL MOUNTING SYSTEM

With its robust design, the i-trap 150EX LED is recommended for use in areas with a potential danger of a gas explosion or a dust explosion. The unit can be wall mounted. Has a specially designed front grid which optimizes the attraction potential.



**ALCOCHEM**  
HYGIENE

# Energy savings & effective fly control go hand in hand

## **i-trap 150EX LED wall mounting**

With its robust design, the i-trap 150EX II is recommended for use in areas with a potential danger of a gas explosion or a dust explosion.

*Easy to service, robust and effective; the i-trap 150EX LED offers it all.*



### **LED lamps**

LED technology offers clear advantages in terms of efficiency (lower energy consumption) and its lifespan (3 years).



### **Glueboards**

Insects are caught on a glue layer, which preserves them over time. The caught insects can be counted and insect species can be analysed, which offers clear advantages in an IPM approach.

## **10 reasons to start using the i-trap 150EX LED:**

### **Functional, industrial design**

Wall-mounted unit featuring a full stainless-steel housing.

### **Powerful LED technology**

Equipped with 2x ASTRON 18W LED lamps and an effective glueboard for fast, discreet capture of flying insects.

### **Optimised attraction performance**

Lamp output is specifically tuned to match the fly's visual spectrum, ensuring maximum attraction efficiency.

### **30% higher effectiveness**

Outperforms conventional units thanks to a unique attraction grid that reflects light onto the landing area, stimulating insect landing behaviour.

### **Durable, high-quality construction**

IP67 - design for demanding industrial environments.

### **Wide coverage area**

Provides effective protection against flying insects for areas up to 150 m<sup>2</sup>.

### **Easy maintenance and servicing**

Designed for fast and simple cleaning, servicing, and replacement.

### **Certified for hazardous environments**

Approved for use in gas and dust explosion-proof ATEX environments.

### **Low operating costs**

UV-A LED lamps offer an energy saving of 30–50% compared to fluorescent lamps.

### **Enhanced UV-A light output**

High-frequency light pulses prevent insects from distinguishing the lamp from natural UV-A light, increasing attraction.

## **Technical specifications**

<b>Area coverage</b>	: 100 - 150 m <sup>2</sup> effective coverage
<b>Light sources</b>	: 2x 18 Watt ASTRON II LED lamps
<b>Type of UV lamps</b>	: UV-A Lamp RoHS certified
<b>Electrical supply</b>	: 100-277 V ~ 50-60 Hz
<b>Catch specifications</b>	: By means of effective glueboard
<b>Power consumption</b>	: 30 Watt
<b>Weight</b>	: 8 Kg
<b>Material</b>	: 0,8 mm SS 304 (Brushed steel)
<b>Degree of protection</b>	: IP67
<b>Guarantee</b>	: 2 year return to base
<b>Lamp life time</b>	: 25.000 hrs
<b>Dimensions (LxHxD)</b>	: 780 x 415 x 160 mm
<b>CE-approval</b>	: Yes
<b>Mounting position</b>	: Wall mounted
<b>Cable &amp; plug</b>	: Not included in scope of supply
<b>Packaging</b>	: Strong cardboard box
<b>Coding</b>	: Ex II 2 GD Ex e mb q IIC T4 T_amb 55°C
<b>Certificate number</b>	: EC Type Examination Certificate Baseefa 04 ATEX 0220
<b>Zone classification</b>	: Zone 1 and 21 areas to EN60079-10-1 & EN60079-10-2 installation EN60079-14
<b>ATEX classification</b>	: Group II Category 2 GD



2.05.0905 - 2026-01